

ELECTRICAL ACCESSORIES

Three pole isolation switch

Provides local isolation of fans with or without timers whilst the rest of the circuit remains live. Enables repair or routine maintenance of fans.

Model no.	Electrical supply	Rating	Size (H x W)	£
FIS	230v 1Ph 50Hz	6A	87mm x 87mm	11.67



Single gang surface mounting box

Model no.	Size (H x W x D)	£
SGB	87mm x 87mm x 25mm	1.20



Enclosed isolators

Model no.	No. of poles	Rating	Size (H x W x D)	£
EI16A-3P	3	16A	167mm x 100mm x 120mm	24.64
EI25A-3P	3	25A	167mm x 100mm x 120mm	25.35
EI32A-3P	3	32A	167mm x 100mm x 120mm	27.39
EI40A-3P	3	40A	167mm x 100mm x 120mm	40.54

Features

- IP65 degree of protection
- Padlockable handle
- Polycarbonate housing

Model no.	No. of poles	Rating	Size (H x W x D)	£
EI16A-4P	4	16A	167mm x 100mm x 120mm	54.64
EI32A-4P	4	32A	167mm x 100mm x 120mm	59.50
EI40A-4P	4	40A	167mm x 100mm x 120mm	77.24



Relay interface

Multi use relay interface that accepts 230v to operate a set of changeover contacts. Uses include:

Where the switching device e.g. PIR and the load e.g. fan motor are on separate circuits
Where changeover contacts are required e.g. for 2 speed motors

Model no.	Rating	Size (H x W)	£
RLI5A	5A	87mm x 87mm x 32mm	28.11
RLI10A	10A	87mm x 87mm x 32mm	32.41



Contactor interface stations

A range of contactor interface stations for use with switching devices such as thermostats, PIR detectors, timeswitches and other ancillaries where the loading exceeds the rating of the switching device. The contactor interface stations can also be used where the switching of a 3 phase load is required.

Larger current rated models available on request.

Model no.	Rating	Size (H x W x D)	Mounting	£
CI9	9A	185mm x 88mm x 120mm	Surface	35.88
CI12	12A	185mm x 88mm x 120mm	Surface	52.57
CI18	18A	202mm x 88mm x 135mm	Surface	72.26

